
XMLmind XML Editor - XHTML Support

Hussein Shafie, Pixware

December 2, 2005

Table of Contents

1. XHTML menu	1
1.1. Convert Document sub-menu	2
2. Custom bindings	3
3. Table rendering	3

1. XHTML menu

Table editing commands fully support HTML 4 tables.

Insert Column Before

Implicitly or explicitly selected element must be a `td` or `th` or the descendant of a `td` or `th`. Inserts a column before column containing specified cell.

A table cell is specified by implicitly or explicitly selecting the table cell or any of its descendants.

Insert Column After

Implicitly or explicitly selected element must be a `td` or `th` or the descendant of a `td` or `th`. Inserts a column after column containing specified cell.

Delete Column

Implicitly or explicitly selected element must be a `td` or `th` or the descendant of a `td` or `th`. Deletes column containing specified cell.

Insert Row Before

Implicitly or explicitly selected element must be a `td` or `th` or the descendant of a `td` or `th`. Inserts a row before row containing specified cell.

Rows editing commands are enabled, not only by implicitly or explicitly selecting a table cell or any of its descendants, but also by explicitly selecting a table row.

Insert Row After

Implicitly or explicitly selected element must be a `td` or `th` or the descendant of a `td` or `th`. Inserts a row before row containing specified cell.

Delete Row

Implicitly or explicitly selected element must be a `td` or `th` or the descendant of a `td` or `th`. Deletes row containing specified cell.

Go to Opposite Link End

A `a` element with one of `href`, `name` or `id` attributes must be implicitly or explicitly selected. Scrolls to and selects opposite link end (if found). For example, will scroll to and select `` if the command has been invoked with `` selected.

Go to Next Link

A `a` element with a `href` attribute must be implicitly or explicitly selected. Scrolls to and selects following similar link (if found). For example, will scroll to and select next `` if the command has been invoked with `` selected.

Go to Previous Link

A `a` element with a `href` attribute must be implicitly or explicitly selected. Scrolls to and selects preceding similar link (if found). For example, will scroll to and select previous `` if the command has been invoked with `` selected.



Preview

Preview document being edited using currently running web browser. Web browser is started if it is not already running.

The temporary preview file (`__PREVIEW__document_name.html`) is generated in the same directory than the document being edited.

On Linux, as configured by XMLmind, this command assumes that the `mozilla` command is referenced in `$PATH`. Of course, this can be changed by modifying the proper configuration file. For example, in order to use Firefox, suffice to add this snippet to your `~/.xxe/addon/customize.xxe`:

```
<property name="XXE_HTML_PREVIEW_COMMAND">/opt/firefox/firefox "%U"</property>
```

1.1. Convert Document sub-menu

Convert to RTF...

Converts the document being edited to RTF (Rich Text Format) using XMLmind FO Converter Personal Edition (see <http://www.xmlmind.com/foconverter>).

The RTF document generated by this command can be edited and printed using Microsoft® Word 2000 and above.

Convert to WordprocessingML...

Converts the document being edited to WordprocessingML using XMLmind FO Converter Personal Edition (see <http://www.xmlmind.com/foconverter>).

The WordprocessingML document generated by this command can be edited and printed using Microsoft® Word 2003 and above.

Print PostScript...

Converts the document being edited to PostScript® using RenderX XEP (see <http://www.renderx.com/>), if its plug-in has been installed, and Apache FOP otherwise (see <http://xml.apache.org/fop>), and then sends the generated file to the chosen printer.

Convert to PDF...

Converts the document being edited to PDF (Adobe® Portable Document Format, also known as Acrobat®) using RenderX XEP (see <http://www.renderx.com/>), if its plug-in has been installed, and Apache FOP otherwise (see <http://xml.apache.org/fop>).

These commands, as any command using a FO processor plug-in, need XMLmind XML Editor Professional Edition in order to be executed successfully.

All the above **Convert** commands display the URL chooser dialog box rather than the standard file chooser dialog box. That is, you must specify the URL (Uniform Resource Locator) of a save file.

Note that these commands can create directories on the fly, if needed to. For example, if you specify `http://www.acme.com/docs/report43/mydoc.pdf` as the URL of the save file and if directory `report43/` does not exist, this directory will be created during command execution.

Uploading the files generated by these commands to a FTP or WebDAV server is only possible with XMLmind XML Editor Professional Edition.

2. Custom bindings

Keystroke	Action
Enter	Inside a <code>p</code> , splits the <code>p</code> in two parts. Elsewhere, normal behaviour.
Del	At the end of a <code>p</code> , if there is no node or text selection, joins this <code>p</code> with following sibling <code>p</code> if any. Otherwise, normal behaviour.
BackSpace	At the beginning of a <code>p</code> , if there is no node or text selection, joins this <code>p</code> with preceding sibling <code>p</code> if any. Otherwise, normal behaviour.
Ctrl-Enter	Inside a <code>p</code> , <code>li</code> , <code>dt</code> , <code>dd</code> , inserts same element after this one. Note that in the case of <code>dt</code> and <code>dd</code> , it inserts a new <code>dt</code> followed by a new <code>dd</code> . Elsewhere, no effect.
Shift-Ctrl-Enter	Inside a <code>p</code> , <code>li</code> , <code>dt</code> , <code>dd</code> , inserts same element before this one. Note that in the case of <code>dt</code> and <code>dd</code> , it inserts a new <code>dt</code> followed by a new <code>dd</code> . Elsewhere, no effect.
Shift-Enter	Inserts a <code>br</code> at caret and moves caret after inserted <code>br</code> .

Application Event	Action
file-drop	On a <code>a</code> element with attribute <code>href</code> , changes the value of the attribute to the URL of the dropped file. Elsewhere, opens the dropped file in the editor.

3. Table rendering

Deprecated attributes (specified in the transitional DTD) are not supported. The following attributes (specified in the strict DTD) are either completely ignored or partially supported. All other attributes (specified in the strict DTD) are supported.

Attribute	Support
<code>table width</code>	Ignored.
<code>table border</code>	Value larger than 1 treated like 1.
<code>table cellspacing</code>	Ignored.
<code>table cellpadding</code>	Ignored.
<code>col (or colgroup) width</code>	All forms including "20%", "3*" or "0*" are supported. A column must contain at least one cell with a column span equal to 1 for the <code>width</code> attribute to have an effect.
<code>align</code>	Values <code>justify</code> and <code>char</code> are rendered like <code>left</code> .
<code>char</code>	Ignored. See <code>align</code> .
<code>charoff</code>	Ignored. See <code>align</code> .